

XR 380 Beam

Model: PR-2345A

RoHS | CE | WDMX | 8m | IP20 | T_c80°C | T_a45°C |




Version: 20211108

Moving Heads



Beam

Fixed gobos



17Kg Size(mm)

Specifications

- Input voltage
200V~240V AC, 50/60Hz
- Power Consumption
600W@230V
Power factor PF>0.90
- Light Source
Lamp MSD Platinum 300S Flex
Color temperature 7800K
rated life 6000hrs
- Colors
1color wheel: 14colors+ Open
- fixed gobo wheel
17gobos+open, gobo diameter=6mm, its thickness=0.8mm
- Prism/Frost
1 8-facet prism and 1 16-facet prism, bi-directional rotation
from slow to fast , both can be overlapped
- Focus
DMX linear focus
- Dimmer/Strobe
Strobe at variable speeds(15 F.P.S at maximum)
0-100% linear dimmer
- Head Movement
Pan 540°, Tilt 270° with 16 bit control
- Beam Angle
0°~2°
- Control
International standard DMX 512 protocol, 5-pin interface
14channels in short mode and 16channels in standard
mode

- Housing
High temperature and anti-UV ABS and aluminum , IP20
- Net Weight
17Kg
- Physical
Ambient temperature at maximum: 45°C
- Accessories
Safety cord, 1 pc
clamp, 2 pcs
Foldable clamp , 2 pcs

■ Light Output

